

Euler(P1300)Specifications

ITEM		SPECIFICATION
Appearance	Model	P1300-CN/JP/US/EU/UK/AUS
	Weight	9.9Kg
	Size	258mm*175mm*249.5mm
	Color	Sliver Black
Battery	Type	Lithium-ion battery
	Energy	1160Wh/
Display	Size	2.8 inch
	Type	HD LCD color screen
	Contents	SOC/ Power/ Remain Time/ Fault Code/ Charge discharge type
Mode	Select energy saving or normal mode	Release button-Saving mode Press button-Normal mode
AC	Output Voltage	110V/220V Pure sine wave (According to the factory settings of different countries and regions)
	Output Power	Max 1300W
	AC Socket AC	4 US/JP 2 CN 1EU/UK/AUS
	Output protection	Short circuit or output power over 1500W
	Frequency	60Hz/50Hz manual switch
USB-A	USB-A Number	2
	USB-A Output voltage	5V
	USB-A Output current	≤2.4A
USB-A QC3.0	USB-A Number	1
	USB	QC3.0
	USB-A Output voltage	5-12V
	USB-A Output power	Max 18W
USB-C PD3.0	USB-C Number	1
	USB	PD3.0
	USB-C Output voltage	5-20V
	USB-C Output power	Max 60W
CIG	Output port	1
	Plug type	Cigar lighter
	Output voltage	12V
	Output power	Max 120W
LED	Bright mode/LED Power	LIGHT-A:Low 2W LIGHT-B:High 3W LIGHT-C:SOS 2W LIGHT-D:Flash 2W LIGHT-E: Breath 2W
Charge	Adapter	DC 8020 48V 6A ≤288W 4h Full Charge
	MPPT	XT60 18-21V 5A,≤100W 14h Full Charge 28-32V 8A,≤200W 6h Full Charge 36-43V 8A,≤300W 4h Full Charge
	CIG	XT60 12-15V 7A ≤100W 14h Full Charge
Temperature	Temperature range	-20°C~60°C / -4°F~140°F

